Product information

SUNOCO



4T GP Sport

Description

Partly synthetic engine oil, reinforced with the latest additive technologies. Useable in 4 stroke motorcycles under both varying conditions as well as extremely high speeds and/or loads.

Application

Specifically recommended for 4 stroke motorcycles of following makes: HONDA, KAWASAKI, MOTTO GUZZI, SUZUKI, TRIUMPH, YAMAHA,... Useable for sport / competition riding! Perfectly suitable for the lubrication of the engine integrated clutch with common oil bath.

- Specifications SAE 10W-40
 - API SJ
 - ACEA A3
 - CCMC G5
 - JASO MA

Properties

- Provides excellent lubrication as well at very low temperatures, as at very high temperatures.
- No deposits from high speed operation and/or high loads.
- Low in volatile fractions.
- Exhaust gas catalyser compatibility

Typical analysis:

Density at 15°C 0.874

Viscosity at 40°C / cSt 98

Viscosity at 100°C / cSt 14.7

Viscosity at -20°C / cP 3300

Flash point °C 240

Pour point °C -36

TBN mg KOH/g 9.4

Noack volatility % 11.8

Colour L3.0

All technical data is provided for reference only. 6 - 2009

Sunoco Danmark European Oil ApS Troensevej 7 9220 Aalborg Ø

Tel.: +45 70 26 15 26