Product information

SUNOCO

4T Moto HD



Description

High quality multigrade type engine lubricant based on high quality mineral base oil, this for 4 stroke Harley Davidson motorbikes operating under both variable conditions as well as with continuously high speeds.

Application

In Harley Davidson motorbikes. Particularly suitable for the "touring / tourist" type and / or "chopper" like rider . Specifically recommended for several models of HARLEY DAVIDSON make, particularly when operated in high environmental temperature areas.

- Specifications mineral oil composition
 - API CE / SAE 20W50
 - typical 19,5 cSt well high in SAE 50 specification range

Properties

- excellent protection against wear and corrosion through the perfectly resistant oil film resulting in high serviceability and extended lifetime.
- prevents formation of deposits on engine parts.
- perfect lubrication at all ambient and high temperature conditions.
- fully compatible with/ not harmful to exhaust gas catalytic convertors .

Typical analysis:

Density at 15°C 0.892

Viscosity at 40°C / cSt 175

Viscosity at 100°C / cSt 19.5

Viscosity at -15°C / cP 8000

Flash point °C 220

Pour point °C -30

TBN mg KOH/g 8.5

Colour 5.5

All technical data is provided for reference only. 6 - 2009

Sunoco Danmark European Oil ApS Troensevej 7 9220 Aalborg Ø

Tel.: +45 70 26 15 26